

PRODUCT DATASHEET

PLANTASTAR 400 W E40

PLANTASTAR-T | High-pressure sodium vapor lamps for open and enclosed luminaires



AREAS OF APPLICATION

- Greenhouses
- Suitable for growth of fruit due to emission of photosynthesis optimised light
- Application only in suitable luminaires

PRODUCT BENEFITS

- Shorter production times
- Control over blossoming

PRODUCT FEATURES

- Average lifetime: 12,000 h
- Provides light for the photosynthesis in plants
- Photon flux: > 90 % after 12,000 h
- High-pressure sodium lamp especially for greenhouse lighting



TECHNICAL DATA

Electrical data



Rated wattage	400.00 W
Lamp current	4.52 A
Nominal wattage	400.00 W
Nominal voltage	100 V
Ignition voltage	4.0 / 5.0 kVp ¹⁾

¹⁾ Minimum / Maximum

Photometrical data

Photon flux	725 µmol/s
Photon flux efficacy	1.7 µmol/s/W
Color temperature	2000 K
Rated LLMF at 2,000 h	0.98
Rated LLMF at 4,000 h	0.97
Rated LLMF at 6,000 h	0.96
Rated LLMF at 8,000 h	0.95
Rated LLMF at 12,000 h	0.94
Rated LLMF at 16,000 h	0.94
Luminous flux	56500 lm
Color rendering index Ra	25

Dimensions & weight



E40
IEC 7004-24
DIN 49625

Diameter	47.0 mm
Length	285.0 mm
Light center length (LCL)	175.0 mm
Product weight	162.00 g

Temperatures & operating conditions

Maximum permitted outer bulb temperature	400 °C
Maximum permitted base edge temperature	250 °C

Lifespan

Rated lamp survival factor at 2,000 h	0.99
Rated lamp survival factor at 4,000 h	0.99
Rated lamp survival factor at 6,000 h	0.98
Rated lamp survival factor at 8,000 h	0.98
Rated lamp survival factor at 12,000 h	0.97
Lifespan B50	32000 h
Lifespan B10	24000 h
Lifespan B5	20000 h

Additional product data

Base (standard designation)	E40
Design / version	Clear
Mercury content	21.0 mg ¹⁾

¹⁾ Maximum

Capabilities

Dimmable	No
Burning position	Any
Enclosed luminaire required	No


Certificates & standards

Energy efficiency class	A++
Energy efficiency class	A++
Energy consumption	440 kWh/1000h


Country-specific categorizations

ILCOS	ST-400-H/E-E40-47/285
-------	-----------------------

Light Distribution



Spectral power distribution



Circuit diagram

LOGISTICAL DATA

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4050300620084	PLANTASTAR 400 W E40	Shipping carton box 12	268 mm x 345 mm x 221 mm	20.43 dm ³	2694.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.